



CODEMARK™

Product Description

HomeGuard TMB, 0.2mm sheet polymer matrix with Bifenthrin incorporated. Used in full underslab termite management system installations and critical joints.

HomeGuard DPC, 0.5mm sheet polymer matrix with Bifenthrin incorporated. Used in perimeter (cavity) termite management system installations.

HomeGuard Blue, 0.25mm sheet polymer matrix with Bifenthrin incorporated. Used in perimeter (cavity) termite management system installations.

HomeGuard GT, Polymer matrix disks typically 5mm in diameter and 2 mm thick with Bifenthrin incorporated in it. Used in perimeter (cavity) termite management system installations.

HomeGuard Collars (40mm 50mm, 80mm, 100mm), rigid plastic collars with Bifenthrin incorporated. Used as a termite management system for penetrations

Product Purpose or Use

An underslab, perimeter and penetration system to deter concealed entry by subterranean termites into a building.

Certificate Holder

FMC Australasia Pty Ltd
ABN 45 095 326 891
26/8 Metroplex Avenue
Murrarie QLD 4172

CodeMark Certification Body

SAI Global Certification Services Pty Limited
(ACN 108 716 669) Trading as "SAI Global"
JAS-ANZ Accreditation No. Z1440295AS
Address: 286 Sussex Street, Sydney, NSW 2000
Website: www.saiglobal.com

CERTIFICATE OF CONFORMITY

This is to certify that

HomeGuard Precision Termite Management System



Complies with the Building Code of Australia (BCA):

1. Volume One: BP1.1 and BP1.2 *(limited only to actions by subterranean termites)*
2. Volume Two: P2.1 *(limited only to actions by subterranean termites)*
3. State Additions: Volume Two: QLD P2.1.1 *(limited only to actions by subterranean termites)*

Subject to the following conditions and limitations:

1. The FMC HomeGuard Precision Termite Management System is to be installed by licensed installers trained and approved by FMC Australasia Pty Ltd.
2. The FMC HomeGuard Precision Termite Management System is to be installed in accordance with FMC HomeGuard installation manual version 3 2008.
3. The HomeGuard DPC, HomeGuard Blue and HomeGuard GT when used across a perimeter cavity must finish at least 75mm above the surrounding finished ground level.
4. Penetrations of a different size to the preformed HomeGuard collar are to be protected using the HomeGuard sheet collars made as described in the installation manual
5. The HomeGuard collars are not to be glued to any of the penetrations that they protect as described in the installation manual.
6. The concrete slab must be constructed in accordance with the requirements of AS 2870-1996 Residential slabs and footings - Construction (as amended up to and including Amdt 4, May 2003) or AS 3600 2001 - Concrete Structures (as amended up to and including Amdt 2, October 2004).
7. Inspections are undertaken annually in accordance with the FMC HomeGuard installation manual to determine that no bridging or breaching of the termite management system has occurred.

Alex Ezrakhovich
General Manager Certification
For and on behalf of SAI Global

22/04/2009

Reissue
Date

19/07/2007

Original
Date of Issue

18/07/2010

Date of Expiry

SAIG-07-CM20003

Certificate Number



- This Certificate of Conformity is issued under arrangement with JAS-ANZ. The ABCB does not in any way warrant or represent that the Product the subject of this Certificate of Conformity conforms with the BCA, nor accepts any liability arising out of the use of the Product.
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the ABCB website, www.abcb.gov.au.